

REMARKS

This Preliminary Amendment cancels the original claims, without prejudice, in the underlying PCT Application No. PCT/EP2004/052836. The Preliminary Amendment also adds new claims 10-19. The new claims conform the claims to U.S. Patent and Trademark Office rules and do not add new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.


The underlying PCT Application No. PCT/EP2004/052836 includes an International Search Report, dated February 2, 2005, a copy of which is submitted herewith.

Applicant asserts that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully submitted,

KENYON & KENYON LLP

Dated: 6/16/06

By: 
Gerard A. Messina
(Reg. No. 35,952)

One Broadway
New York, NY 10004
(212) 425-7200

WINDOW-INTEGRATED ANTENNA IN VEHICLES

Field Of The Invention

The present invention is directed to a window-integrated antenna in vehicles including a heating field which is provided for both FM reception as well as LMS reception.

Background Information

5 The heating field of the window is frequently used in vehicle antennas as the antenna structure. The heating field is provided for both FM and TV reception in ~~US~~United States Patent No. 6,498,588 B1 and in ~~WO~~PCT Published International Application No. 99/66587. A conductor loop, which is not connected to the heating field, is additionally provided for LMS (long, medium, short wave) reception on the upper edge of the window.

10 A significant disadvantage of such a system is the necessity of a surface, e.g., in the upper area of the window, which, due to non-existing heating conductors, cannot be heated and therefore cannot be defrosted. The available heatable area is unacceptably small, particularly in passenger cars having small windows.

The heating conductors run essentially horizontally and essentially parallel to the metallic
15 boundaries of the window. Interference in the vehicle electrical system, transferred by the heating current to the heating conductors acting as the antenna, must, as is known, be suppressed via modules having a high-resistance behavior at high frequencies when the antenna connection point is galvanically linked to the heating field. For FM reception, these modules are one core double chokes, for example, which are integrated into the heating
20 current-supplying conductor segments and, as a rule, are situated at the heating current terminals of the heating field.

For LMS reception, this is a current-compensated toroidal core choke (AM blocking circuit) which is also situated in the heating current supply lead. This AM blocking circuit is a very cost-intensive module whose dead weight of approximately 200g results in high mechanical
25 stresses on the printed circuit board as well as the union points, and is thus to be valued extremely critical with respect to quality assurance. The vibrations, occurring during normal driving conditions, result in the fact that soldered joints are extremely stressed. In compact

vehicles, this AM blocking circuit is frequently mounted in the tailgate, so that accelerations of approximately 50g may occur when the tailgate is slammed shut and the module breaks off the union points.

In other vehicle antenna reception systems, the reception of LMS and diverse FM signals is implemented via conductor structures in one or multiple window panes which are for the most part situated in the immediate proximity of, but spatially separated from, one another. A significant disadvantage in such a system is the necessity of at least two, for the most part fixed, window panes which results in increased expenses for the manufacture of the panes, for the electronic design of connected, for the most part active circuit components, and for the assembly of appropriate circuit carriers.

Antenna systems are also known which form the antennas for LMS and FM reception from the galvanically contacted heating field. Here also, filter elements, which decouple the vehicle electrical system, are necessary for the antenna connection point and the heating conductor (EP 0269723 B1, EP 0382895 B1 *European Published Patent Application No. 0 269 723 and European Published Patent Application No. 0 382 895*).

Advantages of the Summary Of The Invention

Using the measures according to Claim 1, i.e., using a heating conductor field which is provided for FM reception, and possibly TV reception, as well as for LMS reception via one single window, at least one decoupling element being provided for at least the LMS reception which has a high-frequency, but non-galvanic connection to the heating field and the decoupling element being situated in the heating conductor field, in particular between two adjacent heating conductors, the reception of LMS and in particular diverse FM/TV signals is possible via one single window without omitting complete heating of the entire window, in particular in the area not covered by black print. At the same time, the filter elements necessary for the LMS radio broadcast may be omitted, or the filter elements may be designed at a substantial cost advantage compared to previous systems. A separate analysis of the occurring mechanical stress on this module may be omitted and the quality of the system using cost-effective filter modules may be ensured over the vehicle's service life. The basic noise of the antenna for LMS radio reception may be substantially reduced by retaining filter elements for the LMS range.

The conductor structure is applied to a window via common methods, it being irrelevant in terms of the present invention whether a single-pane safety glass or laminated safety glass is used. The window in question is surrounded by a metallic frame and is, for the most part, designed as the rear window of a motor vehicle. However, the described system may also be used on any other window, e.g., in ships.

The particular advantage of the present invention is the fact that, for decoupling the LMS antenna function from the interference of the vehicle electrical system, either no special filter elements in the form of a current-compensated toroidal core choke (high-frequency, low-resistance module) are necessary, or the basic noise during LMS reception is substantially reduced when filter elements for LMS reception are retained.

In addition to the heating conductors used for defrosting, simply one decoupling element, preferably one additional conductor or an additional conductor loop, is inserted in particular between two parallel running heating conductors, as a rule between the upper two, because the technical performance of the reception system is optimal in this way, in such a way that no galvanic link exists between this conductor and the heating field. Due to the non-galvanic link, interference of the vehicle electrical system has a small influence on the basic noise of the antenna. The capacitive coupling between the heating field and the additional conductor is so minor for LMS frequencies, that interference of the vehicle electrical system in the heating current has practically no or only a negligible influence. However, the capacitive coupling for FM and TV frequencies is sufficiently high so that the antenna signals are received using the entire heating conductor structure. Filter elements are necessary here. Due to the high capacitive coupling, the antenna function is comparable to a system in which the antenna connection point is galvanically linked to the heating field. In addition, the entire window is heatable since no structures outside the heating conductor field are necessary.

Cost-effective manufacture is another advantage of the design according to the present invention. In contrast to other embodiments, only one single window pane needs to be manufactured. Another advantage is the integrated and thus simple configuration of passive and active circuit components which provide separate signal paths for the different frequency bands, but which may be placed in one single housing. In addition to a minimum of mechanical components, this also results in minimal wiring.

Drawing

~~Exemplary embodiments of the present invention are explained in greater detail on the basis of the drawing.~~

Brief Description Of The Drawings

Figure 1 shows an integrated antenna system for LMS, FM, and possibly TV reception according to the present invention.

Figure 2 shows another exemplary embodiment including another FM/TV antenna signal decoupling.

Figure 3 shows a comparison of the reception level in the LMS frequency range.

Detailed Description of Exemplary Embodiments

Figure 1 shows a window-integrated antenna made up of heating conductors 3, running parallel to one another, which each meet a busbar 4 at their left and right ends. The heating conductor field formed in this way is supplied with heating current via an FM/TV choke 5 in the supply leads (Ub heating). Depending on the acceptance of the basic noise, an AM blocking circuit 13 having more or less expensive filters is or is not provided. Antenna connection point 1 for FM/TV and LMS signals is galvanically linked with a decoupling element 5 in the heating conductor field but not with the heating conductor field. Decoupling element 6 may be designed as a straight-line conductor, as an open conductor loop as shown in Figure 1, or as a closed conductor loop, or a combination of the latter elements. A structure as long as possible is advantageous. Decoupling element 6 is situated in particular between two adjacent heating conductors 3 and runs parallel (legs of the open conductor loop) to the entire length of both heating conductors 3. The distance of decoupling element 6 or its conductor segments parallel to heating conductors 3 should be as small as possible, in order to ensure a capacitive coupling for FM/TV frequencies. Grounding point 9 for the connection of active antenna module 7 is advantageously located in the direct proximity of antenna connection point 1 in the right upper corner of the heating conductor field on metallic frame 8 surrounding the window (shown in a dashed line).

The heating conductor structure of the window is designed in such a way that a resonant structure for FM frequencies is created at antenna connection point 1, e.g., via additional vertical crossing lines 10 which are galvanically connected to the parallel heating conductors at

each crossing point and are situated on the equi-potential points formed by the voltage distribution.

The decoupled antenna signals are separately amplified (AM, FM, TV1) in electronics module 7 and, if needed, filtered and supplied to TV tuner 11 or radio 12.

5 Figure 2 shows another exemplary embodiment in which another FM/TV antenna signal decoupling is formed from antenna connection point 2, galvanically linked to the heating field on the opposite side, and a close-by ground terminal, thereby forming a dual-antenna system. Additional antennas may be formed from the heating field at another location, e.g., two
10 additional antennas to generate a quadruple-antenna system. This makes it possible to scan a further FM or TV range, to operate a second FM receiver, or a diversity effect due to different reception signals at the two antenna connection points 1 and 2 may be utilized, such as the one which may occur under unfavorable reception conditions during mobile use.

A further advantage of the present invention becomes apparent at this point:

The capacitance of the antenna conductor vis-à-vis the chassis ground is a deciding factor in
15 LMS reception. In the system according to the related art, the overall capacitance of the system with regard to antenna connection 1 is increased in a dual-antenna system by connecting a second electronic module having a certain input capacitance. In other words, part of the received LMS signal is diverted toward ground via the second module, thereby impairing the overall reception. This circumstance is prevented in the antenna system according to the
20 present invention.

Measurements show that the reception of LMS signals using the system according to the present invention shown in Figure 1 is comparable to a system in which the antenna connection point is galvanically linked with the heating field at the upper outer corner. It becomes apparent here that an open conductor loop, as shown in Figure 1, yields the best results. The reception
25 level is marginally lower, but a lower basic noise is generated by the heating current in exchange.

The reception performance for FM/TV reception is comparable to known systems.

Abstract Of The Disclosure

In a window-integrated antenna in vehicles, the heating conductor field (3,4) is used for FM reception as well as for LMS reception. At least one decoupling element (6) is provided for LMS reception which has a high-frequency, but non-galvanic connection to the heating conductor field (3,4). The decoupling element (6) is situated in the heating conductor field, in particular between two adjacent heating conductors (3).

(Figure 1)